



7 DAY
QUICKSHIP

REFERENCE GUIDE
MARCH 2020

FLUXWERX⁷

7 DAY QUICKSHIP

EASY. FAST. SIMPLE.

Our 7 Day Quickship program offers a wide range of made to order LED luminaires and options with fast order processing and expedited shipping across North America.

fluxwerx.com/quickship

LINEAR SUSPENDED					
NO ADDER	APERTURE (APC) (APS)	PROFILE MINI (PM1) (PM3)	PROFILE (PF1) (PF3)	VIEW (VU1)	LOOP (LS1) (LS3)
ENDCAP	(F) Flat	(B) Bevel	(B) Beam	(R) Radius	
	(R) Radius	(F) Flat	(R) Radius	(S) Square	
			(S) Square		
DISTRIBUTION	(A) 75Up / 25Dn	(A) 40Up / 60Dn	(A) 70Up / 30Dn	(A) 65Up / 35Dn	
	(B) 100Dn	(B) 100 Dn	(B) 20Up / 80Dn	(B) 100 Dn	
	(D) 25Up / 75Dn	(D) 20Up / 80Dn		(B) Indep Up / Dn	
		(F) 65Up / 35Dn			
		(B) Indep Up / Dn			
ENERGY		(Z) 14W			
	(A) 17W	(A) 18W		(A) 19W	
	(B) 21W	(B) 22W		(B) 23W	
	(C) 26W	(C) 28W		(C) 29W	
	(D) 34W	(D) 36W		(D) 38W	
CCT		(35) 3500K (40) 4000K			
FINISH		(A) Clear Anodized (W) White Powdercoat			
CEILING		(G) Grid (D) Drywall (S) Structure (R) Remote			
DRIVER		(F1) Non-Dim			
		(F2) 0-10V Dim 3%			
		(E1) eldoLED Eco 0-10V Dim 1%			
VOLTAGE		(M) 120 - 277 V			
SUSPENSION		(03) < 3FT (06) < 6FT (12) < 12FT (25) < 25FT			
LENGTH		(04) 4FT (06) 6FT (08) 8FT (XX) >8FT Runs in 2FT Increments			
OPTIONS		(A) Alternate Wiring			
		(B) Battery Pack			
		(C) Chicago Plenum			

LINEAR RECESSED	
NO ADDER	NOTCH 2 (NT1) AREA
CEILING	(D2) Drywall - Trimless
	(G1) Grid - 9/16" or 15/16" Flat-T
	(G1) Grid - 9/16" Tegular
	(G1) Bolt - Slot
WALL	(W2) Wall - Trimless
DISTRIBUTION	(A) Asymmetric
	(B) Symmetric
ENERGY	(A) 5W/FT
	(B) 6W/FT
	(C) 7.25W/FT
	(D) 9.5W/FT
CCT	(35) 3500K
	(40) 4000K
DRIVER	(F1) Non-Dim
	(F2) 0-10V Dim 3%
	(E1) eldoLED Eco 0-10V Dim 1%
VOLTAGE	(M) 120 - 277 V
LENGTH	(XX) 2FT+ (Increments: 1FT in Drywall, 2FT in Grid)
OPTIONS	(A) Alternate Wiring
	(B) Battery Pack
	(C) Chicago Plenum
	(M) EM or NL (2nd neutral)
	(P) Capsule Endcap
	(T) Throughwire Circuit
	(U) Throughwire (w/neutral)

RECESSED				
NO ADDER	INBOX (NB1) 4-SIDED	TRANSOM (TR1)	RAILS (RA1)	LOOP (LR1)
SIZE	(22) 2x2			
ENERGY	(A) 23W	(A) 22W	(A) 19W	
	(B) 29W	(B) 28W	(B) 23W	
	(C) 38W	(C) 36W	(C) 29W	
	(D) 47W		(D) 38W	
CCT	(35) 3500K			
	(40) 4000K			
DRIVER	(F1) Non-Dim			
	(F2) 0-10V Dim 3%			
	(E1) eldoLED Eco 0-10V Dim 1%			
VOLTAGE	(M) 120 - 277 V			
OPTIONS	(B) Battery Pack			
	(C) Chicago Plenum			

FLUXWERX®

604.549.9379
serviceteam@fluxwerx.com

MARCH 2020